

open DN

ECON® Fire fighting valve Type: 2058 Bronze Angle Pattern **Flange**

Characteristics

Type: 2058

Construction type: Angle pattern Housing material: Bronze Material quality: CC491K (RG5)

Surface protection: Standard manufacturers coating

Connection: Flange

Connection 2: Storz coupling

Flange finish: Flat face

Operation: Hand wheel, non-rising with non-rising

Type of bonnet: Flanged Colour: Red. RAL3000

Spindle material: Chromium steel Primary spindle seal material: EPDM Material bonnet: CC491K [RG5] **Bonnet gasket material: EPDM** Material storz coupling: Brass Actuator material: EN-JL1030

Minimum medium temperature (continuous): -10 °C Maximum medium temperature (continuous): 80 °C Maximum pressure difference at 20 °C: 10 bar

Application

• Recommended in: Utilities

DN	Α	u	H (open)	М	Lug distance	Weight
mm	mm	mm	mm	mm	mm	kg
40	150	140	190	120	51	7.3
50	165	150	190	120	66	8.4
65	185	165	220	140	81	11.6

Pressure class	Maximum medium temperature		
PN10	80 ℃		

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC011418_0002_MVD_EN_18.04.2024