

## Fire fighting valve Type: 907 Bronze Inclined Flange

### Characteristics

**Type:** 907  
**Construction type:** Inclined  
**Housing material:** Bronze  
**Material quality:** CC491K [RG5]  
**Surface protection:** Standard manufacturers coating  
**Connection:** Flange  
**Connection 2:** Storz coupling  
**Flange finish:** Flat face  
**Operation:** Hand wheel, rising with rising stem  
**Type of bonnet:** Screwed  
**Colour:** Red, RAL3000  
**Disc material:** Brass  
**Spindle material:** CuZn35Ni [SoMs59]

**Material bonnet:** CuZn39Pb3 [CW614N]

**Material storz coupling:** Brass

**Actuator material:** EN-JL1030


**Minimum medium temperature (continuous):** -10 °C

**Maximum medium temperature (continuous):** 60 °C

**Maximum pressure difference at 20 °C:** 16 bar

### Application

- Recommended in: Food & Beverages, Maritime, Utilities



DN	A	L3	H2	M	Cam distance	Weight
[mm]	mm	mm	mm	mm	mm	[kg]
25	115	84	140	80	31	1,9
32	140	87	155	80	44	2,9
40	150	100	185	80	52	3,9
50	165	120	195	100	66	5,1
65	185	127	230	120	81	6,4
80	200	157	265	160	89	10,1

Pressure rating	Max. medium temperature
PN16	60°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.