



## Fire fighting valve Type: 906 Brass Inclined External thread (BSPP)

### Characteristics

**Type:** 906  
**Construction type:** Inclined  
**Housing material:** Brass  
**Connection:** External thread (BSPP)  
**Connection 2:** External thread (BSPP)  
**Operation:** Hand wheel, rising with rising stem  
**Type of bonnet:** Screwed  
**Spindle material:** G-CuZn37Pb  
**Material bonnet:** Brass  
**Actuator material:** EN-JL1030

**Minimum medium temperature (continuous):** -10 °C  
**Maximum medium temperature (continuous):** 60 °C  
**Maximum pressure difference at 20 °C:** 16 bar

### Application

- Recommended in: Food & Beverages, Maritime, Utilities

DN ["]	H (open) mm	M mm	Weight [kg]
1 ½	161	80	1,6
2	177	100	2
2 ½	211	100	3,9

Pressure rating	Max. medium temperature
PN16	60°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.