


Fire fighting valve Type: 905 Bronze Inclined External thread (BSPP)



Characteristics

Type: 905
Construction type: Inclined
Housing material: Bronze
Material quality: CC491K (RG5)
Surface protection: Standard manufacturers coating
Connection: External thread (BSPP)
Connection 2: Storz coupling
Operation: Hand wheel, rising with rising stem
Type of bonnet: Screwed
Colour: Red, RAL3000
Disc material: Brass
Spindle material: CuZn35Ni (SoMs59)
Material bonnet: CuZn39Pb3 (CW614N)

Material storz coupling: Brass

Actuator material: EN-JL1030

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 60 °C

Maximum pressure difference at 20 °C: 16 bar

Application

- Recommended in: Food & Beverages, Maritime, Utilities

DN ["]	L2 mm	H2 (open) mm	M mm	Cam distance mm	Weight [kg]
1	84	145	80	31	1
1 ¼	87	160	80	44	1,9
1 ½	100	190	100	52	2,6
2	120	200	120	81	3,5
2 ½	127	240	120	81	4,3
3	157	275	140	89	6,9

Pressure rating

PN16

Max. medium temperature

60°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.