

Fire fighting valve Type: 905 Bronze Inclined External thread (BSPP)

Characteristics

Type: 905

H2

open

Construction type: Inclined Housing material: Bronze Material quality: CC491K (RG5)

Surface protection: Standard manufacturers coating

Connection: External thread (BSPP) Connection 2: Storz coupling

Operation: Hand wheel, rising with rising stem

Type of bonnet: Screwed Colour: Red, RAL3000 Material disc: Brass

Spindle material: CuZn35Ni (SoMs59)

Material bonnet: CuZn39Pb3 (CW614N)

Material storz coupling: Brass Actuator material: EN-JL1030

Minimum medium temperature (continuous): -10 $^{\circ}\text{C}$ Maximum medium temperature (continuous): 60 °C Maximum pressure difference at 20 °C: 16 bar

Application

• Recommended in: Utilities

DN	L2	H2 (open)	М	Lug distance	Weight
	mm	mm	mm	mm	kg
1"	84	145	80	31	1
11⁄4"	87	160	80	44	1.9
1½"	100	190	100	51	2.6
2"	120	200	120	81	3.5
21/2"	127	240	120	81	4.3
3"	157	275	140	89	6.9

Pressure class	Maximum medium temperature
PN16	60 °C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

PR_EC011418_0009_MVD_EN_25.04.2024