



Fire fighting valve Type: 902 Bronze Straight Internal thread (BSPP)

Characteristics

Type: 902

Construction type: Straight

Housing material: Bronze

Material quality: CC491K [RG5]

Surface protection: Standard manufacturers coating

Connection: Internal thread [BSPP]

Connection 2: Storz coupling

Operation: Hand wheel, rising with rising stem

Type of bonnet: Screwed

Colour: Red, RAL3000

Disc material: Brass

Spindle material: CuZn35Ni [SoMs59]

Material bonnet: CuZn39Pb3 [CW614N]

Material storz coupling: Brass

Actuator material: EN-JL1030


Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 60 °C

Maximum pressure difference at 20 °C: 16 bar

Application

- Recommended in: Food & Beverages, Maritime, Utilities



DN ["]	L [mm]	H (open) mm	M mm	Cam distance mm	Weight [kg]
1	118	110	80	31	1
1 ¼	130	125	80	44	1,9
1 ½	138	140	100	52	2,7
2	176	160	120	81	3,7
2 ½	212	195	120	81	5,5
3	225	200	140	89	8

Pressure rating

PN16

Max. medium temperature

60°C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.