



OVENTROP Regulating valve Series: Hydrocontrol VFC Type: 2620 Static Cast iron Flange

Characteristics

Series: Hydrocontrol VFC

Type: 2620

Housing material: Cast iron

Material quality: EN-JL1040

Surface protection: Coated

Connection: Flange

Type of control gear: Static

Application: CH water

With measuring nipples: Yes

Material disc: CC491K

Spindle material: Brass

Material bonnet: CC491K

Nipple material: Brass

Minimum medium temperature (continuous): -10 °C

Maximum medium temperature (continuous): 150 °C

With drain: No

With position indicator: Yes

Application

- Recommended in: Utilities




Fig. 2621

DN [mm]	L mm	H mm	D mm
20	150	118	105
25	160	118	115
32	180	136	140
40	200	136	150
50	230	145	165
65	290	188	185
80	310	203	200
100	350	240	220
125	400	283	250
150	480	285	285
200	600	467	340
250	730	480	405
300	850	515	460

Min./Max.	Press./Temp.
Max.oper. press.	16bar
Min. temp.	-10 °C
Max. temp.	150 °C

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.