


ECON® Check valve Type: 501 Brass Internal thread (BSPP) PN30

Brass ball check valve with spring, pressure class PN30.



Characteristics

- Type:** 501
- Norm:** EN (DIN)
- Construction type:** Straight
- Housing material:** Brass
- Connection:** Internal thread (BSPP)
- Face to Face norm:** Manufacturer standard
- With spring:** Yes
- Maximum pressure difference at 20 °C:** 30 bar

Application

- General industry.
- Neutral, clean viscous liquids.
- Oils.
- Suitable for horizontal and vertical (rising flow) mounting.

Options

- Available in stainless steel; type 501RVS (only in 1/2").

DN	L [mm]	Weight [kg]	Kv-value [m³/h]	Opening pressure [bar]
3/8"	55	0.4	2	± 0,35
1/2"	60	0.4	4	± 0,35
3/4"	75	0.4	8	± 0,35
Max operating pressure 30 bar				

Nominal inner diameter	Pressure rating	Face to Face length mm	Valve shape	Kv value m³/h	Sealing	Material disc	Spring material	Minimum medium temperature [continuous] °C	Maximum medium temperature [continuous] °C	Article
3/8" [10]	PN30	55	Ball	2	Stainless steel	Stainless steel	Stainless steel	-10	220	EC0050103/8-MK41
1/2" [15]	PN30	60	Ball	4	Stainless steel	Stainless steel	Stainless steel	-10	220	EC0050101/2-MK41
3/4" [20]	PN30	75	Ball	8	Stainless steel	Stainless steel	Stainless steel	-10	220	EC0050103/4-MK41

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.