

NORGREN Filter-regulator EXCELON® automatic drain series B73G

- Excelon design allows in-line installation or modular installation with other Excelon products
- High efficiency water and particle removal
- Quick release bayonet bowl
- Push to lock adjusting knob with tamper resistant accessory

Characteristics

Series: Excelon Type: B73G Function: Filter-Regulator Bowl Material: Polycarbonate Operating temperature: -34 / 80 °C Material seal: Neoprene Filter element material: Sintered polypropylene

Port thread type	Port Size	Filtration level	With pressure gauge	Drain type	Max. inlet pressure	Adjustment range	Housing material	Article
	in	μ m			bar			
BSPP (G)	1/2	40	No	Automatic	17	0.3 - 10 bar	Aluminium	B73G-4GK-AD3- RMN
BSPP (G)	1/2	40	No	Automatic	10	0.3 - 10 bar	Aluminium	B73G-4GK-AT3- RMN
BSPP (G)	1/2	40	No	Automatic	10	0.3 - 10 bar	Aluminium	B73G-4GK-AP3- RMN
BSPP (G)	1/4	40	No	Automatic	10	0.3 - 10 bar	Aluminium	B73G-2GK-AT3- RMN
BSPP (G)	1/4	40	No	Automatic	17	0.3 - 10 bar	Aluminium	B73G-2GK-AD3- RMN
BSPP (G)	3/8	40	No	Automatic	10	0.3 - 10 bar	Aluminium	B73G-3GK-AT3- RMN
BSPP (G)	3/8	5	No	Automatic	10	0.3 - 10 bar	Aluminium	B73G-3GK-AD1- RMN

PR_EC011549_0031_JB_EN_22.05.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1



T

