



NORGREN Filter-regulator EXCELON® automatic drain series B74G

- Excelon design allows in-line installation or modular installation with other Excelon products
- High efficiency water and particle removal
- Quick release bayonet bowl
- Push to lock adjusting knob with tamper resistant accessory

Characteristics

Series: Excelon

Type: B74G

Function: Filter-Regulator

Bowl Material: Polycarbonate

Operating temperature: -34 / 80 °C

Adjustment range: 0.3 - 10 bar

Material seal: NBR

Filter element material: Sintered polypropylene

Membrane material: PU

Port thread type	Port Size in	Filtration level µm	With pressure gauge	Drain type	Self-venting	Maximum operating pressure	Max. inlet pressure bar	Flow rate l/min	Housing material	Article
BSPP [G]	3/8	40	No	Automatic	Yes	10	10	6	Aluminium	B74G-3GK-AP3-RMN
BSPP [G]	1/2	40	No	Automatic	Yes	17	17	6	Aluminium	B74G-4GK-AD3-RMN
BSPP [G]	1/2	40	No	Automatic	Yes	10	10	6	Aluminium	B74G-4GK-AP3-RMN
BSPP [G]	3/4	40	No	Automatic	Yes	10	10	6	Aluminium	B74G-6GK-AP3-RMN
NPT	40	No	Automatic	Yes	17					B74G-4AK-AD3-RMN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.