

SPIRAX SARCO Thermodynamic steam trap fig. 1062 series TD32F stainless steel flange



Characteristics

Serie: TD32F

Type: 1062

Construction type: Straight

Housing material: Stainless steel

Pressure rating: PN40

With built-in filter: Yes





Fig.	DN ["/mm]	A [mm]	H mm	L mm	Weight [kg]
1062L - 1062 LA	15	95	55	150	2,3
1062L - 1062 LA	20	105	60	150	3
1062L - 1062 LA	25	115	65	160	4,1
1062H	15	95	55	150	2,4
1062H	20	105	60	150	3,1
1062H	25	115	65	160	4,2
1062HA	15	95	55	150	2,4

Max. pressure	32 bar
Min. pressure	0,25bar (1062L & 1062H)
Min. pressure with anti air-binding disc	0,8 bar (1062LA & 1062HA)
Max. back pressure	80% from inlet pressure
Max. temperature	400°C
Max. temperature with anti air-binding disc	255°C

Nominal inner diameter	Connection	Capacity type	With automatic de-aerator	Article
DN15	Flange	H	No	EC010620015R18Q
DN15	Flange	H	Yes	EC010620015R1QQ
DN15	Flange	LC	No	EC010620015R1VQ
DN15	Flange	LC	Yes	EC010620015R1XQ
DN20	Flange	H	No	EC010620020R18Q
DN20	Flange	LC	Yes	EC010620020R1XQ
DN25	Flange	H	No	EC010620025R18Q

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.