

FENNER Wedge belt Ultra PLUS wrapped narrow section SPB



Fenner
®

Ultra PLUS
Medium duty, wrapped wedge belt

Designed for use in single or multi-belt drives, Fenner® Ultra PLUS transmission belts deliver maximum cost and performance benefits by utilising low elongation polyester cords and abrasion resistant impregnated jacket fabric.

Characteristics

Series: Ultra PLUS

Type: SPB

Height: 13 mm

Width (top): 16 mm

Material: CR (polychloroprene)

Tensile Cord: Polyester (PES)

Sheathed: Yes

Shape-toothed model: No

Double V-profile model: No

With perforation: 0

With top layer: No

Temperature resistance: -55 / 70 °C

Execution

- Ideal for use in single or multi-belt drives ► One-shot tensioning for fit and forget reliability

Approval

- Fully approved by all international standards
 - BS 3790 (British Standard) ► ISO 4184 (International Standards Organisation) ► DIN 7753 (German Institute for Standardization) ► Static conductive in accordance with ISO 1813 ► Conforms to API (American Petroleum Institute) specifications

Technical Information

- Extended temperature range -55° to +70°C. ► PB® (Precision Built) technology, eliminating the need for matching ► Conditionally oil resistant

Reference length (ISO) mm	Article
1250	SPB1250-FEN
1320	SPB1320-FEN
1340	SPB1340-FEN
1360	SPB1360-FEN
1400	SPB1400-FEN
1410	SPB1410-FEN
1450	SPB1450-FEN
1500	SPB1500-FEN
1550	SPB1550-FEN
1600	SPB1600-FEN
1650	SPB1650-FEN
1670	SPB1670-FEN
1700	SPB1700-FEN
1750	SPB1750-FEN
1800	SPB1800-FEN
1850	SPB1850-FEN
1900	SPB1900-FEN
1950	SPB1950-FEN
1980	SPB1980-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO)	Article
mm	
2000	SPB2000-FEN
2020	SPB2020-FEN
2060	SPB2060-FEN
2120	SPB2120-FEN
2150	SPB2150-FEN
2180	SPB2180-FEN
2240	SPB2240-FEN
2280	SPB2280-FEN
2300	SPB2300-FEN
2310	SPB2310-FEN
2360	SPB2360-FEN
2410	SPB2410-FEN
2430	SPB2430-FEN
2450	SPB2450-FEN
2500	SPB2500-FEN
2530	SPB2530-FEN
2580	SPB2580-FEN
2600	SPB2600-FEN
2650	SPB2650-FEN
2680	SPB2680-FEN
2720	SPB2720-FEN
2800	SPB2800-FEN
2840	SPB2840-FEN
2900	SPB2900-FEN
3000	SPB3000-FEN
3070	SPB3070-FEN
3150	SPB3150-FEN
3170	SPB3170-FEN
3250	SPB3250-FEN
3350	SPB3350-FEN
3450	SPB3450-FEN
3500	SPB3500-FEN
3550	SPB3550-FEN
3620	SPB3620-FEN
3650	SPB3650-FEN
3750	SPB3750-FEN
3800	SPB3800-FEN
3870	SPB3870-FEN
4000	SPB4000-FEN
4060	SPB4060-FEN
4120	SPB4120-FEN
4250	SPB4250-FEN
4310	SPB4310-FEN
4500	SPB4500-FEN
4560	SPB4560-FEN
4750	SPB4750-FEN
4820	SPB4820-FEN
5000	SPB5000-FEN
5070	SPB5070-FEN
5300	SPB5300-FEN
5380	SPB5380-FEN
5600	SPB5600-FEN
5680	SPB5680-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Reference length (ISO)	Article
mm	
5900	SPB5900-FEN
6000	SPB6000-FEN
6300	SPB6300-FEN
6340	SPB6340-FEN
6700	SPB6700-FEN
7100	SPB7100-FEN
7500	SPB7500-FEN
8000	SPB8000-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.