



NORGREN Short stroke cylinder single acting series RM/91000/M

- One third the basic length of a corresponding ISO/VDMA model
- Low friction, long life seal design
- Fully non-corrodible specification
- Standard magnetic piston

Characteristics

Series: RM/91000/M
Function: Single acting
Magnetic: Yes
Barrel material: Anodised aluminium
Operating temperature: -5 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
RM/91020/M/10	Without	20	10	M 5		2 / 10	RM/91020/M/10
RM/91032/M/10	Without	32	10		G1/8	2 / 10	RM/91032/M/10
RM/91032/M/15	Without	32	15		G1/8	2 / 10	RM/91032/M/15
RM/91032/M/25	Without	32	25		G1/8	2 / 10	RM/91032/M/25
RM/91040/M/10	Without	40	10		G1/8	2 / 10	RM/91040/M/10
RM/91050/M/25	Without	50	25		G1/8	2 / 10	RM/91050/M/25
RM/91063/M/25	Without	63	25		G1/4	2 / 10	RM/91063/M/25

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.