



NORGREN Compact air bellow single acting series PM/31000

- Frictionless operation
- No maintenance or lubrication
- Ideal for short stroke, high-force applications
- High vibration isolation level
- Easy, compact installation

Characteristics

Series: PM/31000
Function: Single acting
Magnetic: No
Operating temperature: -30 / 50 °C

Manufacturer ID	Stroke length mm	Port Size in	Operating pressure bar	Article
PM/31041	40	G3/8	0 / 8	PM/31041
PM/31042	80	G3/8	0 / 8	PM/31042
PM/31061	55	G1/2	0 / 8	PM/31061
PM/31062	115	G1/2	0 / 8	PM/31062
PM/31081	95	G3/4	0 / 8	PM/31081
PM/31082	185	G3/4	0 / 8	PM/31082
PM/31091	105	G3/4	0 / 8	PM/31091
PM/31121	105	G3/4	0 / 8	PM/31121
PM/31122	215	G3/4	0 / 8	PM/31122
PM/31021	20	G1/4	0 / 8	PM/31021
PM/31022	45	G1/4	0 / 8	PM/31022
PM/31023	65	G1/4	0 / 8	PM/31023

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.