

NORGREN ISO Roundline cylinder single acting series RM/28000/M



- Magnetic piston as standard
- Generally conforms to ISO 6432
- High strength, double crimped end cap design
- Corrosion resistant
- Nose mounting nut and piston rod locknut as standard

Characteristics

Series: RM/28000/M
Function: Single acting
Magnetic: Yes
Barrel material: Stainless steel
Operating temperature: -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in		
RM/28016/M/10	Mechanical	16	10	M 5		2 / 10	RM/28016/M/10
RM/28016/M/50	Mechanical	16	50	M 5		2 / 10	RM/28016/M/50
RM/28020/M/25	Mechanical	20	25		G1/8	2 / 10	RM/28020/M/25
RM/28020/M/50	Mechanical	20	50		G1/8	2 / 10	RM/28020/M/50
RM/28025/M/10	Mechanical	25	10		G1/8	2 / 10	RM/28025/M/10
RM/28025/M/25	Mechanical	25	25		G1/8	2 / 10	RM/28025/M/25
RM/28025/M/50	Mechanical	25	50		G1/8	2 / 10	RM/28025/M/50

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.