



NORGREN Repairable roundline cylinder double acting series M/6000

- Rugged, compact units
- Integral rear eye mounting
- Corrosion resistant construction
- Synthetic rubber buffers at end of stroke

Characteristics

Series: Martonair
Type: M/6000
Function: Double acting
Magnetic: No
Barrel material: Aluminium
Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in		
M/6010/15	Mechanical	10	15	M 5		2 / 10	M/6010/15
M/6016/15	Mechanical	16	15	M 5		2 / 10	M/6016/15
M/6016/25	Mechanical	16	25	M 5		2 / 10	M/6016/25
M/6020/10	Mechanical	20	10		G1/8	2 / 10	M/6020/10
M/6020/25	Mechanical	20	25		G1/8	2 / 10	M/6020/25
M/6020/75	Mechanical	20	75		G1/8	2 / 10	M/6020/75
M/6020/100	Mechanical	20	100		G1/8	2 / 10	M/6020/100
M/6025/20	Mechanical	25	20		G1/8	2 / 10	M/6025/20
M/6025/25	Mechanical	25	25		G1/8	2 / 10	M/6025/25
M/6025/50	Mechanical	25	50		G1/8	2 / 10	M/6025/50
M/6025/75	Mechanical	25	75		G1/8	2 / 10	M/6025/75
M/6025/100	Mechanical	25	100		G1/8	2 / 10	M/6025/100

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.