

NORGREN Roundline cylinder double acting series RM/55401/M



- Clean line design
- Low friction, long life seals
- Standard magnetic piston for full control system versatility
- Non-lube operation

Characteristics

Series: RM/55401/M

Function: Double acting

Magnetic: Yes

Barrel material: Anodised aluminium

Operating temperature: -20 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
RM/55433/M/50	Adjustable	32	50	G1/8	1 / 10	RM/55433/M/50
RM/55433/M/80	Adjustable	32	80	G1/8	1 / 10	RM/55433/M/80
RM/55433/M/100	Adjustable	32	100	G1/8	1 / 10	RM/55433/M/100
RM/55433/M/160	Adjustable	32	160	G1/8	1 / 10	RM/55433/M/160
RM/55441/M/25	Adjustable	40	25	G1/4	1 / 10	RM/55441/M/25
RM/55441/M/50	Adjustable	40	50	G1/4	1 / 10	RM/55441/M/50
RM/55441/M/80	Adjustable	40	80	G1/4	1 / 10	RM/55441/M/80
RM/55441/M/100	Adjustable	40	100	G1/4	1 / 10	RM/55441/M/100
RM/55441/M/125	Adjustable	40	125	G1/4	1 / 10	RM/55441/M/125
RM/55441/M/160	Adjustable	40	160	G1/4	1 / 10	RM/55441/M/160
RM/55441/M/200	Adjustable	40	200	G1/4	1 / 10	RM/55441/M/200
RM/55451/M/80	Adjustable	50	80	G1/4	1 / 10	RM/55451/M/80
RM/55451/M/100	Adjustable	50	100	G1/4	1 / 10	RM/55451/M/100
RM/55464/M/100	Adjustable	63	100	G3/8	1 / 10	RM/55464/M/100

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.