

NORGREN Roundline cylinder single acting series RT/57300/M



- Saves 20% space over the basic length of a corresponding ISO/VDMA cylinder
- Low friction, long life seals
- High strength, double crimped end cap design
- Standard magnetic piston for full control system versatility

Characteristics

Series: RT/57300/M
Function: Single acting
Magnetic: Yes
Barrel material: Stainless steel
Operating temperature: -5 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
RT/57316/M/25	Mechanical	16	25	M 5		2 / 10	RT/57316/M/25
	Mechanical	25	25		Rc1/8	2 / 10	RT/57325/MC/25
RT/57325/M/25	Mechanical	25	25		Rc1/8	2 / 10	RT/57325/M/25
RT/57325/M/50	Mechanical	25	50		Rc1/8	2 / 10	RT/57325/M/50

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.