



NORGREN Roundline cylinder double acting series RT/57200/M

- Saves 20% space over the basic length of a corresponding ISO/VDMA cylinder
- Low friction, long life seals
- High strength, double crimped end cap design
- Standard magnetic piston for full control system versatility

Characteristics

Series: RT/57200/M

Function: Double acting

Magnetic: Yes

Barrel material: Stainless steel

Operating temperature: -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure bar	Article
		mm	mm	mm	in		
RT/57210/M/10	Mechanical	10	10	M 5		1 / 10	RT/57210/M/10
RT/57210/M/25	Mechanical	10	25	M 5		1 / 10	RT/57210/M/25
RT/57210/M/40	Mechanical	10	40	M 5		1 / 10	RT/57210/M/40
RT/57212/M/10	Mechanical	12	10	M 5		1 / 10	RT/57212/M/10
RT/57212/M/25	Mechanical	12	25	M 5		1 / 10	RT/57212/M/25
RT/57212/M/40	Mechanical	12	40	M 5		1 / 10	RT/57212/M/40
RT/57212/M/50	Mechanical	12	50	M 5		1 / 10	RT/57212/M/50
RT/57216/M/10	Mechanical	16	10	M 5		1 / 10	RT/57216/M/10
RT/57216/M/25	Mechanical	16	25	M 5		1 / 10	RT/57216/M/25
RT/57216/M/40	Mechanical	16	40	M 5		1 / 10	RT/57216/M/40
RT/57216/M/50	Mechanical	16	50	M 5		1 / 10	RT/57216/M/50
RT/57216/M/80	Mechanical	16	80	M 5		1 / 10	RT/57216/M/80
RT/57220/M/10	Mechanical	20	10		Rc1/8	1 / 10	RT/57220/M/10
RT/57220/M/20	Mechanical	20	20		Rc1/8	1 / 10	RT/57220/M/20
RT/57220/M/40	Mechanical	20	40		Rc1/8	1 / 10	RT/57220/M/40
RT/57220/M/50	Mechanical	20	50		Rc1/8	1 / 10	RT/57220/M/50
RT/57220/M/80	Mechanical	20	80		Rc1/8	1 / 10	RT/57220/M/80
RT/57220/M/100	Mechanical	20	100		Rc1/8	1 / 10	RT/57220/M/100
RT/57220/M/160	Mechanical	20	160		Rc1/8	1 / 10	RT/57220/M/160
RT/57220/M/200	Mechanical	20	200		Rc1/8	1 / 10	RT/57220/M/200
RT/57225/M/10	Mechanical	25	10		Rc1/8	1 / 10	RT/57225/M/10
RT/57225/M/25	Mechanical	25	25		Rc1/8	1 / 10	RT/57225/M/25
RT/57225/M/40	Mechanical	25	40		Rc1/8	1 / 10	RT/57225/M/40
RT/57225/M/50	Mechanical	25	50		Rc1/8	1 / 10	RT/57225/M/50
RT/57225/M/80	Mechanical	25	80		Rc1/8	1 / 10	RT/57225/M/80
RT/57225/M/100	Mechanical	25	100		Rc1/8	1 / 10	RT/57225/M/100
RT/57225/M/125	Mechanical	25	125		Rc1/8	1 / 10	RT/57225/M/125
RT/57225/M/160	Mechanical	25	160		Rc1/8	1 / 10	RT/57225/M/160
RT/57225/M/200	Mechanical	25	200		Rc1/8	1 / 10	RT/57225/M/200
RT/57232/M/10	Mechanical	32	10		Rc1/8	1 / 10	RT/57232/M/10
RT/57232/M/25	Mechanical	32	25		Rc1/8	1 / 10	RT/57232/M/25
RT/57232/M/40	Mechanical	32	40		Rc1/8	1 / 10	RT/57232/M/40
RT/57232/M/50	Mechanical	32	50		Rc1/8	1 / 10	RT/57232/M/50
RT/57232/M/80	Mechanical	32	80		Rc1/8	1 / 10	RT/57232/M/80
RT/57232/M/100	Mechanical	32	100		Rc1/8	1 / 10	RT/57232/M/100
RT/57232/M/125	Mechanical	32	125		Rc1/8	1 / 10	RT/57232/M/125

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Port Size	Operating pressure	Article
		mm	mm	mm	in	bar	
RT/57232/M/160	Mechanical	32	160		Rc1/8	1 / 10	RT/57232/M/160
RT/57232/M/200	Mechanical	32	200		Rc1/8	1 / 10	RT/57232/M/200
RT/57232/M/250	Mechanical	32	250		Rc1/8	1 / 10	RT/57232/M/250
RT/57232/M/320	Mechanical	32	320		Rc1/8	1 / 10	RT/57232/M/320
RT/57240/M/25	Mechanical	40	25		Rc1/8	1 / 10	RT/57240/M/25
RT/57240/M/40	Mechanical	40	40		Rc1/8	1 / 10	RT/57240/M/40
RT/57240/M/50	Mechanical	40	50		Rc1/8	1 / 10	RT/57240/M/50
RT/57240/M/80	Mechanical	40	80		Rc1/8	1 / 10	RT/57240/M/80
RT/57240/M/100	Mechanical	40	100		Rc1/8	1 / 10	RT/57240/M/100
RT/57240/M/125	Mechanical	40	125		Rc1/8	1 / 10	RT/57240/M/125
RT/57240/M/160	Mechanical	40	160		Rc1/8	1 / 10	RT/57240/M/160
RT/57240/M/200	Mechanical	40	200		Rc1/8	1 / 10	RT/57240/M/200
RT/57240/M/250	Mechanical	40	250		Rc1/8	1 / 10	RT/57240/M/250
RT/57240/M/320	Mechanical	40	320		Rc1/8	1 / 10	RT/57240/M/320
RT/57250/M/25	Mechanical	50	25		Rc1/4	1 / 10	RT/57250/M/25
RT/57250/M/50	Mechanical	50	50		Rc1/4	1 / 10	RT/57250/M/50
RT/57250/M/100	Mechanical	50	100		Rc1/4	1 / 10	RT/57250/M/100
RT/57250/M/125	Mechanical	50	125		Rc1/4	1 / 10	RT/57250/M/125
RT/57250/M/160	Mechanical	50	160		Rc1/4	1 / 10	RT/57250/M/160
RT/57250/M/200	Mechanical	50	200		Rc1/4	1 / 10	RT/57250/M/200
RT/57250/M/320	Mechanical	50	320		Rc1/4	1 / 10	RT/57250/M/320
RT/57263/M/25	Mechanical	63	25		Rc1/4	1 / 10	RT/57263/M/25
RT/57263/M/50	Mechanical	63	50		Rc1/4	1 / 10	RT/57263/M/50
RT/57263/M/80	Mechanical	63	80		Rc1/4	1 / 10	RT/57263/M/80
RT/57263/M/100	Mechanical	63	100		Rc1/4	1 / 10	RT/57263/M/100
RT/57263/M/125	Mechanical	63	125		Rc1/4	1 / 10	RT/57263/M/125
RT/57263/M/160	Mechanical	63	160		Rc1/4	1 / 10	RT/57263/M/160
RT/57263/M/200	Mechanical	63	200		Rc1/4	1 / 10	RT/57263/M/200
RT/57263/M/320	Mechanical	63	320		Rc1/4	1 / 10	RT/57263/M/320

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.