

NORGREN Roundline cylinder double acting series RT/57200/MF



- Saves 20% space over the basic length of a corresponding ISO/VDMA cylinder
- Low friction, long life seals
- High strength, double crimped end cap design
- Standard magnetic piston for full control system versatility

Characteristics

Series: RT/57200/MF
Function: Double acting
Magnetic: Yes
Barrel material: Stainless steel
Operating temperature: -10 / 80 °C

Manufacturer ID	Cushioning	Bore diameter	Stroke length	Port Size	Operating pressure	Article
		mm	mm	in	bar	
RT/57220/MF/25	Mechanical	20	25	Rc1/8	1 / 10	RT/57220/MF/25
RT/57220/MF/50	Mechanical	20	50	Rc1/8	1 / 10	RT/57220/MF/50
RT/57225/MF/40	Mechanical	25	40	Rc1/8	1 / 10	RT/57225/MF/40
RT/57232/MF/50	Mechanical	32	50	Rc1/8	1 / 10	RT/57232/MF/50

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.