

## **SKF Anti-fretting agent LGAF 3E**

- LGAF 3E is a greasy, smooth paste to prevent fretting corrosion caused by very slight oscillations or by vibrations that can make dismounting more difficult. Reduction of fretting corrosion providing easier dismounting of bearings
- Better sliding on designed loose bearing arrangements such as vibrating screens, truck and car wheel bearings
- Easier removal of general industrial components in a wide range of applications such as nuts, bolts, flanges, studs, bearings, guide pins, couplings, jack screws, lathe centres, push rods, and spline shafts

## Characteristics

Series: LGAF 3E

**Application:** Lubrication - grease **Temperature range:** -25 / 250 °C

Colour: Beige

**Droping point:** > 125 °C **Thickener:** Lithium

Base oil type: Mineral/Synthetic

Norm: NLGI 2

Worked penetration 0.1mm: 265-295

Content	Packaging	Article
kg		
0.5	Can	LGAF3E/0.5

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

**ERIKS**