

GFS Guiding pin, size 01 for counterbore type 1479

Design: HSS. Annealed and grinding. The countersink and pin are each clamped by one screw, whereby the countersink is additionally secured against turning by a stud.



Application: Suitable for DIN countersinks and with the corresponding pin/countersink combinations for step holes or countersinks outside of the norm.

Fixed without internal cooling.

Characteristics

Type: 1479

Description	Article
Pilot pin sz.01 2.4mm	W90A-14790240
Pilot pin sz.01 2.5mm	W90A-14790250
Pilot pin sz.01 2.6mm	W90A-14790260
Pilot pin sz.01 2.7mm	W90A-14790270
Pilot pin sz.01 2.8mm	W90A-14790280
Pilot pin sz.01 2.9mm	W90A-14790290
Pilot pin sz.01 3.0mm	W90A-14790300
Pilot pin sz.01 3.1mm	W90A-14790310
Pilot pin sz.01 3.2mm	W90A-14790320
Pilot pin sz.01 3.3mm	W90A-14790330
Pilot pin sz.01 3.4mm	W90A-14790340
Pilot pin sz.01 3.5mm	W90A-14790350
Pilot pin sz.01 3.6mm	W90A-14790360
Pilot pin sz.01 3.7mm	W90A-14790370
Pilot pin sz.01 3.8mm	W90A-14790380
Pilot pin sz.01 3.9mm	W90A-14790390
Pilot pin sz.01 4.0mm	W90A-14790400
Pilot pin sz.01 4.1mm	W90A-14790410
Pilot pin sz.01 4.2mm	W90A-14790420
Pilot pin sz.01 4.4mm	W90A-14790440
Pilot pin sz.01 4.5mm	W90A-14790450

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.