REXNORD VIVA flexible element spacer version type VS



Rexnord Viva Elastomeric Couplings

The most advanced elastomeric coupling available

Rexnord Viva Elastomeric Couplings feature a design based on the proven Rexnord Omega Couplings. Design upgrades to Viva allow for greater torque transmission with a smaller coupling. Incorporating the quality features of Omega, Rexnord Viva Couplings are non-lubricated, material-flexing split-in-half tire couplings. Viva Couplings are built for reliability in a variety of demanding applications including pumps, compressors, blowers, mixers, and more. This all-purpose coupling has excellent vibration damping capability helping to prolong the life of connected equipment.

Characteristics

Series: VIVA Type: VS

Technical Information

- Easy replacement without moving the hubs or connected equipment.
- Capscrews are easily accessible in tight spaces.
- Optimal tensile strength and fatigue resistance.
- Excellent chemical and environmental aging resistance.
- No lubrication required.
- Protects equipment by cushioning schock loads and dampening torsional vibration.
- Accommodates unavoidable misalignment with low reactionary forces.
- No need for coupling disassembly to inspect.
- Close-coupled and spacer coupling hubs are identical allowing reduced inventories.

Construction

- Split-in-half flex element design.
- Radial bolting
- Special formulated polyurethene flex element
- Torsionally soft
- High misalignment capacity
- Visual inspection
- Interchangable hubs

Options

Viva spacer (VS) elastomeric coupling features a split-in-half flex element and reversible hubs with optional hole mounting positions.

- Supplied with metric fastenersHub offered in rough bore, custom bore, and bushed designs
- Connects equipment with shaft gap (distance between shaft end) up to 9.8" (250 mm)
- Accommodates shaft diameters up to 6.5" (165 mm)
- Continuous torque loads up to 55,494 lb-in (6,270
- Available in 12 sizes ranging from VS110 through VS460
- Optional hole mounting positions and reversible hubs accommodate most shaft spacing requirements

Туре	Size	Material	Article
Flexible element	110	Polyurethane	VS110ELEMENT
Flexible element	125	Polyurethane	VS125ELEMENT
Flexible element	130	Polyurethane	VS130ELEMENT
Flexible element	150	Polyurethane	VS150ELEMENT
Flexible element	170	Polyurethane	VS170ELEMENT
Flexible element	190	Polyurethane	VS190ELEMENT
Flexible element	215	Polyurethane	VS215ELEMENT
Flexible element	245	Polyurethane	VS245ELEMENT

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

.RC0023_0027_JLR_EN_19.05.2024