

FENNER HRC Elastomeric coupling hub type B pilot bored


HRC semi-elastic flexible couplings are designed for general purpose use particularly on machinery driven from standard IEC electric motors, due to the interacting dog design the shaft connection is fail safe.



Characteristics

Series: HRC

Type: B



Type	Size	Version	Material	Bore mm	Article
Hub	70	B	Grey cast iron (GG)	8	HRC70B-FEN
Hub	90	B	Grey cast iron (GG)	10	HRC90B-FEN
Hub	110	B	Grey cast iron (GG)	10	HRC110B-FEN
Hub	130	B	Grey cast iron (GG)	15	HRC130B-FEN
Hub	150	B	Grey cast iron (GG)	20	HRC150B-FEN
Hub	180	B	Grey cast iron (GG)	25	HRC180B-FEN
Hub	230	B	Grey cast iron (GG)	25	HRC230B-FEN
Hub	280	B	Grey cast iron (GG)	30	HRC280B-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.