


FENNER HRC Elastomeric coupling hub type F for Taper Lock

HRC semi-elastic flexible couplings are designed for general purpose use particulary on machinery driven from standard IEC electric motors, due to the interacting dog design the shaft connection is fail safe.





Туре	Size	Version	Material	Article
Hub	70	F	Grey cast iron (GG)	HRC70F-FEN
Hub	90	F	Grey cast iron (GG)	HRC90F-FEN
Hub	110	F	Grey cast iron (GG)	HRC110F-FEN
Hub	130	F	Grey cast iron (GG)	HRC130F-FEN
Hub	150	F	Grey cast iron (GG)	HRC150F-FEN
Hub	180	F	Grey cast iron (GG)	HRC180F-FEN
Hub	230	F	Grey cast iron (GG)	HRC230F-FEN
Hub	280	F	Grey cast iron (GG)	HRC280F-FEN

PR_RC0023_0133_JB_EN_03.05.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

T

