



FENNER JAW flexible coupling hub

Fenner Jaw Type Coupling Hub. Also known as Lovejoy or Essex couplings meet the demands for a low cost, general purpose flexible coupling, they cater for incidental misalignment, absorb shock loads and damp out small amplitude vibrations.

Characteristics

Series: JAW

Type: SX

Construction


- Sintered cast iron constructionRange of element materials available including nitrile, urethane and Hytrel

Application


- Ease of alignmentFail-safe shaft connectionPump spacer variant availableDesign powers up to 42.2kW available at 1440rpmAmbient operating temperature range -50°C to +120°C

Execution

- Quick-fit wrap around element available



SX (2 hubs plus spider element)



QF (2 hubs plus QF ring kit)

Type	Size	Version	Material	Bore mm	Article
Hub	35	SX	Cast iron	3	L035HUB/PB-FEN
Hub	50	SX	Cast iron	6	L050HUB/PB-FEN
Hub	70	SX	Cast iron	9	L070HUB/PB-FEN
Hub	75	SX	Cast iron	9	L075HUB/PB-FEN
Hub	90	SX	Cast iron	9	L090HUB/PB-FEN
Hub	95	SX	Cast iron	9	L095HUB/PB-FEN
Hub	100	SX	Cast iron	12	L100HUB/PB-FEN
Hub	110	SX	Cast iron	15	L110HUB/PB-FEN
Hub	150	SX	Cast iron	15	L150HUB/PB-FEN
Hub	190	SX	Cast iron	19	L190HUB/PB-FEN
Hub	225	SX	Cast iron	19	L225HUB/PB-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.