



FENNER V-pulley for taper bush section SPB - 1 groove

Fenner® Taper Lock® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: B/SPB/QXPB

Number of grooves: 1

Bore type: Tapered bore

Pitch circle diameter mm	Taper Lock	Material	Groove width mm	Article
100	1610	Cast iron	16.1	SPB100X1-FEN
125	1610	Cast iron	16.1	SPB125X1-FEN
140	1610	Cast iron	16.1	SPB140X1-FEN
150	1610	Cast iron	16.1	SPB150X1-FEN
160	1610	Cast iron	16.1	SPB160X1-FEN
200	2012	Cast iron	16.1	SPB200X1-FEN
224	2012	Cast iron	16.1	SPB224X1-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.