



FENNER V-pulley for taper bush section SPC - 3 grooves

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: C/SPC/QXPC

Number of grooves: 3

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
17	51	17
	65	10
10	65	10
100	65	100
2	89	2

Pitch circle diameter	Taper Lock	Model	Material	Groove width	K	L	M	Article
mm				mm	mm	mm	mm	
200	2517		Cast iron	22				SPC200X3-FEN
212	3020		Cast iron	22				SPC212X3-FEN
224	3020	3	Cast iron	22	17	51	17	SPC224X3-FEN
236	3020		Cast iron	22				SPC236X3-FEN
250	3020		Cast iron	22				SPC250X3-FEN
265	3525	1	Cast iron	22		65	10	SPC265X3-FEN
280	3525	1	Cast iron	22		65	10	SPC280X3-FEN
300	3525	8	Cast iron	22	10	65	10	SPC300X3-FEN
315	3525	8	Cast iron	22	100	65	100	SPC315X3-FEN
335	3525	8	Cast iron	22	10	65	10	SPC335X3-FEN
355	3525	8	Cast iron	22	10	65	10	SPC355X3-FEN
375	3525	8	Cast iron	22	10	65	10	SPC375X3-FEN
400	3525	4	Cast iron	22	10	65	10	SPC400X3-FEN
425	3525	4	Cast iron	22	10	65	10	SPC425X3-FEN
450	3525	4	Cast iron	22	10	65	10	SPC450X3-FEN
475	3525	4	Cast iron	22	10	65	10	SPC475X3-FEN
500	3525	4	Cast iron	22	10	65	10	SPC500X3-FEN
560	3525	4	Cast iron	22	10	65	10	SPC560X3-FEN
800	4535	4	Cast iron	22	2	89	2	SPC800X3-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.