



FENNER V-pulley for taper bush section SPZ - 1 groove

Fenner ® Taper Lock ® pulleys are manufactured to the DIN 2210, DIN 2211 and ISO 4183 norms, they are designed to operate at rim speeds of up to 40m/sec and (depending on size) to use the short version Fenner Taper Lock bush.

Characteristics

Series: Pulley TL

Type: Z/SPZ/QXPZ

Number of grooves: 1

Bore type: Tapered bore

Size table:

K	L	M
mm	mm	mm
13	22	
	22	
	22	6
	25	9
0	25	9
8	32	8

Pitch circle diameter mm	Taper Lock	Model	Material	Groove width mm	K mm	L mm	M mm	Article
56	1008	9	Cast iron	9.7	13	22		SPZ56X1-FEN
60	1008	9	Cast iron	9.7		22		SPZ60X1-FEN
63	1108	1	Cast iron	9.7		22	6	SPZ63X1-FEN
67	1108		Cast iron	9.7				SPZ67X1-FEN
71	1108		Cast iron	9.7				SPZ71X1-FEN
75	1108	1	Cast iron	9.7		22	6	SPZ75X1-FEN
80	1210		Cast iron	9.7				SPZ80X1-FEN
85	1210	1	Cast iron	9.7		25	9	SPZ85X1-FEN
90	1210	1	Cast iron	9.7		25	9	SPZ90X1-FEN
95	1210		Cast iron	9.7				SPZ95X1-FEN
100	1210		Cast iron	9.7	0	25	9	SPZ100X1-FEN
106	1610		Cast iron	9.7	0	25	9	SPZ106X1-FEN
112	1610		Cast iron	9.7				SPZ112X1-FEN
118	1610		Cast iron	9.7				SPZ118X1-FEN
125	1610		Cast iron	9.7				SPZ125X1-FEN
132	1610		Cast iron	9.7				SPZ132X1-FEN
140	1610		Cast iron	9.7				SPZ140X1-FEN
150	1610		Cast iron	9.7				SPZ150X1-FEN
160	1610		Cast iron	9.7				SPZ160X1-FEN
180	1610		Cast iron	9.7				SPZ180X1-FEN
200	2012		Cast iron	9.7				SPZ200X1-FEN
250	2012		Cast iron	9.7				SPZ250X1-FEN
315	2012	4	Cast iron	9.7	8	32	8	SPZ315X1-FEN

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.