

Boring bar 95 ° E.-SCLCR/L with internal cooling type 2969



Design: Boring bar for insert 7° positive, screw clamping, tool carrier nickel-plated.

Supplied in sets of 4, without inserts, without screwdriver.

Application: Boring.

Designation: A0608H SCLCR 06


Shank-rund(Vollmaterial) d g7: 8 mm

Dimension dia. D min.: 8 mm

Dimension l1: 100 mm

Dimension l2: 25 mm

Dimension f: 4 mm



Designation: A0810J SCLCR 06

Shank-rund(Vollmaterial) d g7: 10 mm

Dimension dia. D min.: 12 mm

Dimension l1: 110 mm

Dimension l2: 32 mm

Dimension f: 6 mm

Designation: A1012K SCLCR 06

Shank-rund(Vollmaterial) d g7: 12 mm

Dimension dia. D min.: 14 mm

Dimension l1: 125 mm

Dimension l2: 38 mm

Dimension f: 7 mm

Designation: A1216M SCLCR 06

Shank-rund(Vollmaterial) d g7: 16 mm

Dimension dia. D min.: 18 mm

Dimension l1: 150 mm

Dimension l2: 50 mm

Dimension f: 9 mm

Description	Article
Boring bar set 95deg. internal cooling A-SCLCR 06	W90A-29695950
SC boring bar 95deg. internal cooling E08K SCLCL 06	W90A-29695966
SC boring bar 95deg. internal cooling E08K SCLCR 06	W90A-29695963
SC boring bar 95deg. internal cooling E10K SCLCL 06	W90A-29695972
SC boring bar 95deg. internal cooling E10K SCLCR 06	W90A-29695969
SC boring bar 95deg. internal cooling E12M SCLCL 06	W90A-29695978
SC boring bar 95deg. internal cooling E12M SCLCR 06	W90A-29695975
SC boring bar 95deg. internal cooling E16M SCLCL 09	W90A-29695990
SC boring bar 95deg. internal cooling E16M SCLCR 09	W90A-29695987

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.