


FORMAT ISO boring bar 95° A.-SCLCR/L with internal cooling type 2969



Design: Boring bar for inserts 7° positive, screw clamping, tool carrier nickel-plated.

Supplied without indexable inserts, without screwdriver.

Application: Boring.



Description	Article
Boring bar 95deg. internal cooling A08F SCLCL 06	W90A-29695855
Boring bar 95deg. internal cooling A08F SCLCR 06	W90A-29695850
Boring bar 95deg. internal cooling A10H SCLCL 06	W90A-29695865
Boring bar 95deg. internal cooling A10H SCLCR 06	W90A-29695860
Boring bar 95deg. internal cooling A12K SCLCL 06	W90A-29695875
Boring bar 95deg. internal cooling A12K SCLCR 06	W90A-29695870
Boring bar 95deg. internal cooling A16M SCLCL 09	W90A-29695885
Boring bar 95deg. internal cooling A16M SCLCR 09	W90A-29695880
Boring bar 95deg. internal cooling A20Q SCLCL 09	W90A-29695895
Boring bar 95deg. internal cooling A20Q SCLCR 09	W90A-29695890
Boring bar 95deg. internal cooling A25Q SCLCL 09	W90A-29695905
Boring bar 95deg. internal cooling A25Q SCLCR 09	W90A-29695900

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.