


FORMAT ISO boring bar 95° A.-SDUCR/L with internal cooling type 2969



Design: Boring bar for inserts 7° positive, screw clamping, tool carrier nickel-plated.

Supplied in sets of 3 without inserts, without screwdriver.

Application: Boring.



Description	Article
Boring bar 93deg. internal cooling A10H SDUCL 07	W90A-29696105
Boring bar 93deg. internal cooling A10H SDUCR 07	W90A-29696100
Boring bar 93deg. internal cooling A12K SDUCL 07	W90A-29696115
Boring bar 93deg. internal cooling A12K SDUCR 07	W90A-29696110
Boring bar 93deg. internal cooling A16M SDUCL 07	W90A-29696125
Boring bar 93deg. internal cooling A16M SDUCR 07	W90A-29696120
Boring bar 93deg. internal cooling A20Q SDUCL 11	W90A-29696135
Boring bar 93deg. internal cooling A20Q SDUCR 11	W90A-29696130
Boring bar 93deg. internal cooling A25Q SDUCL 11	W90A-29696145
Boring bar 93deg. internal cooling A25Q SDUCR 11	W90A-29696140

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.