

FORMAT HR HSSco TiAlN roughing end mill type 2233



HSS
Co8

TiAlN

Typ
HR


Z
3-6

DIN
844-K

Design: DIN 844-K, 30°, up to dia. 20 mm with centre cut.

Applicaiton: Can be used for peripheral milling and drill cutting.

Cutting speed approx. 50% higher than with non-coated tools. Dry machining possible.



Description	Article
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 10mm	W90A-22231000
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 12mm	W90A-22231200
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 14mm	W90A-22231400
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 16mm	W90A-22231600
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 20mm	W90A-22232000
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 4mm	W90A-22230400
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 5mm	W90A-22230500
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 6mm	W90A-22230600
Rough.end mill sh. DIN844HSSCo8 TiALN type HR 8mm	W90A-22230800

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.