

FORMAT NC deburring mill 120° N solid carbide TiAlN type 2449



Design: Solid carbide [K10/K20], type N, according to company standard, similar to DIN 6527, TiAlN-coated.

Application: Can be used for deburring and chamfering edges. Suitable for machining contours.

Cutting speed approx. 50% higher than with non-coated tools. Dry machining possible.

Characteristics

Type: Deburring mill

DIN standard: 6527L

Type	Maximum working length mm	Shaft diameter mm	Total length mm	DIN standard	Article
Deburring mill	8	4	54	6527L	W90A-24490400
Deburring mill	10	6	57	6527L	W90A-24490600
Deburring mill	12	8	63	6527L	W90A-24490800
Deburring mill	14	10	72	6527L	W90A-24491000
Deburring mill	16	12	83	6527L	W90A-24491200
Deburring mill	18	16	92	6527L	W90A-24491600
Deburring mill	20	20	104	6527L	W90A-24492000

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.