



NSK Double-row self-aligning ball bearing Tapered bore Open

Characteristics

Series: 12

Bore: Tapered bore

Sealing: Open

Manufacturer ID	Inner diameter	Outer diameter	Width	Internal clearance	Article
	mm	mm	mm		
1206KTN	30	62	16	CN (normal)	1206K-NSK
1208KTNC3	40	80	18	C3	1208KC3-NSK
1308KJ	40	90	23	CN (normal)	1308KJ-NSK
1209KJC3	45	85	19	C3	1209KJC3-NSK
2209KJ	45	85	23	CN (normal)	2209KJ-NSK
1309KTNC3	45	100	25	C3	1309KC3-NSK
1309KJC3	45	100	25	C3	1309KJC3-NSK
1210KTNC3	50	90	20	C3	1210KC3-NSK
1210KTN	50	90	20	CN (normal)	1210K-NSK
1310KJ	50	110	27	CN (normal)	1310KJ-NSK
2211KJC3	55	100	25	C3	2211KJC3-NSK
2211KJ	55	100	25	CN (normal)	2211KJ-NSK
1311KJC3	55	120	29	C3	1311KJC3-NSK
2311KJC3	55	120	43	C3	2311KJC3-NSK
2313KJ	60	140	46	CN (normal)	2313KJ-NSK
1213KJC3	65	120	23	C3	1213KJC3-NSK
2213KJC3	65	120	31	C3	2213KJC3-NSK
1215KJC3	75	130	25	C3	1215KJC3-NSK
1216KJ	80	140	26	CN (normal)	1216KJ-NSK
2218KJ	90	160	40	CN (normal)	2218KJ-NSK

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.