

SKF Thrust ball bearing Double direction Series: 522

Thrust ball bearings are manufactured as single direction or double direction thrust ball bearings. They are designed to accommodate axial loads only and must not be subjected to any radial load. Thrust ball bearings are separable, i.e. the shaft washer, housing washer(s), ball and cage assembly(s) can be mounted separately. Shaft washers have a ground bore to enable an interference fit. The bore of the housing washer is turned and always larger than the shaft washer bore.

To accommodate initial misalignment between the shaft and housing, both single and double direction thrust ball bearings are available with sphered seat surfaces on the housing washers. They can be used together with a sphered seat washer adjacent to the housing washer or adjacent to a machine component manufactured with a sphered surface.

Double direction thrust ball bearings

Consist of one shaft washer, two housing washers and two ball and cage assemblies. The housing washers and ball and cage assemblies of double direction bearings are identical to those used in single direction bearings. Double direction thrust ball bearings can accommodate axial loads and locate a shaft axially, in both directions.

Characteristics

Series: 522

Variant: Double direction Spherical housing washer: No

Manufacturer ID	Inner diameter	Outer diameter	Height	with seat washer	Article
	mm	mm	mm		
52206	25	52	29	No	52206-SKF
52212	50	95	46	No	52212-SKF
52215	60	110	47	No	52215-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1