

SKF Flanged bushing Maintenance-free Sinterbronze/ Sinterbronze Series: PSMF

• When storing or mounting, the bushing should never come in contact with absorbent material as it may wick the oil away very quickly. Therefore, SKF recommends keeping the bushing in it's original package until just prior to mounting. Additional lubrication is usually not necessary.

Advantages of sintered bronze bushings are:[ul2]very high sliding velocity

- lubrication free
- maintenance-free operation
- good frictional properties
- Applications include:[ul2]electrical equipement
- household equipement
- printing machinery
- machine tools

Characteristics

Series: PSMF With collar: Yes Maintenance: Maintenance-free Tread material: Sinterbronze

Manufacturer ID	Shaft diameter	Outer diameter	Width	Flange diameter	Flange thickness	Article
	mm	mm	mm	mm	mm	
PSMF 101616 A51	10	16	16	22	3	PSMF101616-SKF
PSMF 152212 A51	15	22	12	28	3	PSMF152212-SKF
PSMF 162216 A51	16	22	16	28	3	PSMF162216-SKF
PSMF 253225 A51	25	32	25	39	3.5	PSMF253225-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

