

## SKF Straight bushing Requiring maintenance Phosphor-Zinnbronze (CuSn10P)/Phosphor-Zinnbronze (CuSn10P) **Series: PBM**

• Solid bronze bushings can be lubricated with either oil or grease. The lubricant not only improves the sliding properties, but also reduces wear and prevents corrosion.

Advantages of solid bronze bushings include:[ul2]insensitive to dirty environments

- resistant to shock loads and vibrations at low speed
- good resistance to corrosive contaminants
- equipped with grooves to retain lubricants
- Applications include:[ul2]construction machinery
- transport equipment
- pulp and papermaking machinery
- offshore equipment

## **Characteristics**

Series: PBM With collar: No

Maintenance: Requiring maintenance

Tread material: Phosphor-Zinnbronze (CuSn10P)

Manufacturer ID	Shaft diameter	Outer diameter	Width	Article
	mm	mm	mm	
PBM 304030 M1G1	30	40	30	PBM304030M1G1-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



RC0158\_0012\_EN\_01.05.2024