



SKF V-ring seals for SNL & SE-series bearing housings series TSN..A

- V-ring seals consist of a V-ring and a sheet steel sealing washer with a vulcanized rubber lip. The rubber lip fits into the seal groove in the housing. The washer is protected against corrosion. V-rings can accommodate circumferential speeds up to 7 m/s. For circumferential speeds between 7 and 12 m/s, they should be located axially on the shaft. At speeds above 12 m/s, a support ring must be used to prevent the seal from lifting. Seals per pack: 2
- Material: nitrile rubber, steel
- Temperature range: -40°C to +100°C
- Max. circumferential speed: 7 m/s, 12 m/s for special conditions

Characteristics

Series: TSN..A

Material: NBR/steel

Operating temperature: -40 / 100 °C

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
TSN 505 A	20	41.5	4.8	TSN505A-SKF
TSN 506 A	25	46.5	4.8	TSN506A-SKF
TSN 507 A	30	56.5	4.8	TSN507A-SKF
TSN 508 A	35	61.5	4.8	TSN508A-SKF
TSN 608 A	35	72.5	4.8	TSN608A-SKF
TSN 509 A	40	66.5	4.8	TSN509A-SKF
TSN 609 A	40	77.5	4.8	TSN609A-SKF
TSN 510 A	45	72.5	4.8	TSN510A-SKF
TSN 610 A	45	82.5	4.8	TSN610A-SKF
TSN 208 A	50	55	9	TSN208A-SKF
TSN 511 A	50	77.5	4.8	TSN511A-SKF
TSN 611 A	50	87.5	4.8	TSN611A-SKF
TSN 210 A	54	64	9	TSN210A-SKF
TSN 309 A	55	77.5	4.8	TSN309A-SKF
TSN 512 A	55	82.5	4.8	TSN512A-SKF
TSN 612 A	55	97.5	4.8	TSN612A-SKF
TSN 310 A	60	82.5	4.8	TSN310A-SKF
TSN 513 A	60	87.5	4.8	TSN513A-SKF
TSN 613 A	60	103	4.8	TSN613A-SKF
TSN 212 A	63	75	11	TSN212A-SKF
TSN 311 A	65	87.5	4.8	TSN311A-SKF
TSN 515 A	65	97.5	4.8	TSN515A-SKF
TSN 615 A	65	113	4.8	TSN615A-SKF
TSN 213 A	67	79	11	TSN213A-SKF
TSN 516 A	70	103	4.8	TSN516A-SKF
TSN 313 A	75	103	4.8	TSN313A-SKF
TSN 517 A	75	108	4.8	TSN517A-SKF
TSN 617 A	75	150.5	5.8	TSN617A-SKF
TSN 314 A	80	108	4.8	TSN314A-SKF
TSN 518 A	80	113	4.8	TSN518A-SKF
TSN 315 A	85	113	4.8	TSN315A-SKF
TSN 216 A	90	118.5	4.8	TSN216A-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter	Outer diameter	Width	Article
	mm	mm	mm	
TSN 520 A	90	150.5	5.8	TSN520A-SKF
TSN 620 A	90	170.5	5.8	TSN620A-SKF
TSN 217 A	95	122.5	4.8	TSN217A-SKF
TSN 317 A	95	150.5	5.8	TSN317A-SKF
TSN 522 A	100	160.5	5.8	TSN522A-SKF
TSN 524 A	110	170.5	5.8	TSN524A-SKF
TSN 526 A	115	180.5	5.8	TSN526A-SKF
TSN 528 A	125	190.5	5.8	TSN528A-SKF
TSN 232 A	175	215.5	5.8	TSN232A-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.