



SKF Felt seals for SNL & SE-series bearing housings series TSN..C

- Felt seals are simple and effective. At circumferential speeds above 4 m/s, a small gap forms between the felt and shaft, transforming the contact seal into a non-contact, gap-type seal. Seals per pack: 2
- Material: felt, nitrile rubber, aluminium
- Temperature range: -40°C to +100°C
- Max. circumferential speed: 4 m/s

Characteristics

Series: TSN..C

Material: Felt, NBR, Aluminum

Operating temperature: -40 / 100 °C

Manufacturer ID	Inner diameter mm	Outer diameter mm	Width mm	Article
TSN 506 C	25	42	8	TSN506C-SKF
TSN 606 C	25	52	8	TSN606C-SKF
TSN 507 C	30	52	8	TSN507C-SKF
TSN 508 C	35	57	8	TSN508C-SKF
TSN 608 C	35	68	8	TSN608C-SKF
TSN 509 C	40	62	8	TSN509C-SKF
TSN 510 C	45	68	8	TSN510C-SKF
TSN 511 C	50	73	8	TSN511C-SKF
TSN 611 C	50	83	8	TSN611C-SKF
TSN 512 C	55	78	8	TSN512C-SKF
TSN 513 C	60	83	8	TSN513C-SKF
TSN 515 C	65	93	10	TSN515C-SKF
TSN 516 C	70	98.5	10	TSN516C-SKF
TSN 517 C	75	103.5	10	TSN517C-SKF
TSN 518 C	80	108.5	10	TSN518C-SKF
TSN 520 C	90	143.5	14	TSN520C-SKF
TSN 522 C	100	153.5	14	TSN522C-SKF
TSN 524 C	110	163.5	14	TSN524C-SKF
TSN 526 C	115	173.5	14	TSN526C-SKF
TSN 528 C	125	183.5	14	TSN528C-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.