

SKF Rod end Maintenance-free Steel/PTFE sintered bronze Internal thread right hand Series: SI..C


Design:

Maintenance-free rod end with a threaded shank. With an open bearing (without seals), internal (female) right-hand thread.

Sliding contact surface combination: Steel/PTFE sintered bronze

Suitable for heavy, constant direction loads, where low coefficient of friction is required; limited suitability for alternating loads, shock loads.

Rod end with steel/PTFE sintered bronze sliding contact surface combination contain a bearing from the standard assortment. The outer ring is staked in place in the housing.



Characteristics

Series: Sl..C

Thread type: Internal thread right hand **Maintenance:** Maintenance-free

Sliding contact surface: Steel/PTFE sintered bronze

Manufacturer ID	Inner diameter	Thread size	Article
	mm		
SI 6 C	6	M 6	GIR6UK-SKF
SI 10 C	10	M 10	GIR10UK-SKF
SI 12 C	12	M 12	GIR12UK-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS