

SKF Thrust washer Series: AS

- AS series thin universal washersare 1 mm thick
- are made of spring steel and hardened
- can be used as shaft or housing washers for needle roller thrust bearings in the AXK series
- can be used as shaft washers for bearings in the AXW series
- are available for $4 \le d \le 160 \text{ mm}$

Can be used to provide a cost-effective bearing solution, if adjacent machine components are not hardened, but have adequate stiffness and the requirements to geometrical tolerances are moderate. Both faces of the washers are polished and can be used as raceways.

Characteristics

Series: AS

Manufacturer ID	Inner diameter	Outer diameter	Width	Article
	mm	mm	mm	
AS 1024	10	24	1	AS1024-SKF
AS 1226	12	26	1	AS1226-SKF
AS 2035	20	35	1	AS2035-SKF
AS 3552	35	52	1	AS3552-SKF
AS 4565	45	65	1	AS4565-SKF
AS 5578	55	78	1	AS5578-SKF
AS 6085	60	85	1	AS6085-SKF
AS 6590	65	90	1	AS6590-SKF
AS 85110	85	110	1	AS85110-SKF

PR_RC0187_0008_EN_20.04.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

