




SKF Single row tapered roller bearing Metric

Tapered roller bearings have tapered inner and outer ring raceways and tapered rollers. They are designed to accommodate combined loads, i.e. simultaneously acting radial and axial loads. The projection lines of the raceways meet at a common point on the bearing axis to provide true rolling and low friction. Single row tapered roller bearings are separable, i.e. the inner ring with roller and cage assembly [cone] can be mounted separately from the outer ring [cup].

Characteristics

Series: 302



Manufacturer ID	Inner diameter mm	Cup Outer diameter mm	Total width mm	Article
639209	15	35	11.62	639209-SKF
30302 J2	15	42	14.25	30302-SKF
639177	20	43	13.25	639177-SKF
639174	26	52	15.73	639174-SKF
32206 BJ2/QCL7CVA606	30	62	21.6	32206B-SKF
30207 J2/Q	35	72	18.25	30207-SKF
30307 J2/Q	35	80	23.06	30307-SKF
32307 J2/Q	35	80	32.75	32307-SKF
RBT1B 328915/Q	40	78.961	39.61	RBT1B328915-SKF
32208 J2/Q	40	80	24.75	32208-SKF
BT1B 329270/Q	45	72	19.418	BT1B329270Q-SKF
31309 J2/QCL7C	45	100	27.71	31309-SKF
30210 J2/Q	50	90	22.09	30210-SKF
31310 J2/QCL7C	50	110	29.89	31310-SKF
32011 X/Q	55	90	24.53	32011X-SKF
33111/Q	55	95	31.43	33111-SKF
30312 J2/Q	60	130	34.14	30312-SKF
30214 J2/Q	70	125	26.25	30214-SKF
32214 J2/Q	70	125	33.41	32214-SKF
33017/Q	85	130	36	33017-SKF
32317 J2	85	180	63.5	32317-SKF
32317 BJ2	85	180	63.67	32317B-SKF
33220	100	180	63	33220-SKF
331126/Q	105	170	40.26	331126-SKF
33022	110	170	47	33022-SKF
30222 J2	110	200	42.08	30222-SKF
32024 X	120	180	38	32024X-SKF
33024	120	180	48	33024-SKF
32028 X	140	210	45	32028X-SKF
32030 X	150	225	48	32030X-SKF
32032 X	160	240	51	32032X-SKF
32034 X	170	260	57	32034X-SKF
32036 X	180	280	64	32036X-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Manufacturer ID	Inner diameter	Cup Outer diameter	Total width	Article
	mm	mm	mm	
32938	190	260	45	32938-SKF
32940	200	280	51	32940-SKF
32944	220	300	51	32944-SKF
32052 X	260	400	87	32052X-SKF

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.