



SKF Single-Point automatic lubricator series LAGD

- The units are supplied ready-to-use straight from the box and filled with a wide range of high performance SKF lubricants. Tool-free activation and time-setting allow easy and accurate adjustment of lubrication flow. Flexible dispense rate from 1 to 12 months
- Stoppable or adjustable if required
- Intrinsic safety rating: ATEX approved for zone 0
- Transparent lubricant container allows visual inspection of dispense rate
- Compact size, permits installation in restrictive areas
- Greases and chain oils available



Typical applications

- Applications in restrictive and hazardous locations
- Bearing housing lubrication
- Electric motors
- Fans and pumps
- Conveyors
- Cranes
- Chains (oil)
- Elevators and escalators (oil)

Characteristics

Series: LAGD

Type: LAGD 125/HHT26

Drive mechanism	Container volume ml	Lubricant	Article
Gass cell	60	LGHB 2	LAGD60/HB2
Gass cell	60	LGWA 2	LAGD60/WA2
Gass cell	125	LGHB 2	LAGD125/HB2
Gass cell	125	LGWA 2	LAGD125/WA2

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.