



SKF High viscosity bearing grease with solid lubricants LGEM 2

- LGEM 2 is a high viscosity, mineral oil based grease using a lithium soap. Its content of molybdenum disulphide and graphite provides extra protection for harsh applications subjected to high loads, heavy vibrations and slow rotations. High oxidation stability
- Molybdenum disulphide and graphite provide lubrication even if the oil film breaks down

Typical applications:

- Rolling element bearings running at low speed and very high loads
- Jaw crushers
- Track laying machines
- Lift mast wheels
- Building machines such as mechanical rams, crane arms and crane hooks



Characteristics

Series: LGEM 2

Application: Lubrication - grease

Temperature range: -20 / 120 °C

Colour: Black

Dropping point: > 180 °C

Thickener: Lithium/calcium

Base oil type: Mineral oil

Norm: NLGI 2

DIN standard: DIN 51825 KPF2K-20

Worked penetration 0.1mm: 265-295

Content kg	Packaging	Article
5	Can	LGEM2/5
18	Bucket	LGEM2/18

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.