



SKF High performance high temperature bearing grease LGHP 2

- LGHP 2 is a premium quality mineral oil based grease, using a modern Polyurea (di-urea) thickener. It is suitable for electric motors and similar applications. Extremely long life at high temperatures
- Wide temperature range
- Excellent corrosion protection
- High thermal and mechanical stability
- Good start-up performance at low temperatures
- Compatibility with common polyurea and lithium thickened greases

Low noise properties

Typical applications:

- Electric motors: Small, medium and large
- Industrial fans, including high speed fans
- Water pumps
- Rolling bearings in textile, paper processing and drying machines
- Applications with medium and high speed ball (and roller) bearings operating at medium and high temperatures
- Clutch release bearings
- Vertical shaft applications
- Kiln trucks and rollers



Characteristics

Series: LGHP 2

Application: Lubrication - grease

Temperature range: -40 / 150 °C

Colour: Blue

Dropping point: > 240 °C

Thickener: Polyurea

Base oil type: Mineral oil

Norm: NLGI 2 and 3

DIN standard: DIN 51825 K2N-40

Worked penetration 0.1mm: 245-275

Volume l	Content kg	Packaging	Article
	1	Can	LGHP2/1
	5	Can	LGHP2/5
	18	Bucket	LGHP2/18
	50	Barrel	LGHP2/50
0.42		Cartridge	LGHP2/0.4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.