

SKF General purpose bearing grease LGMT 3

- LGMT 3 is mineral oil based, lithium soap thickened grease. This premium quality, general purpose grease is suitable for a wide range of industrial and automotive applications requiring stiff grease. Excellent rust inhibiting properties
- High oxidation stability within its recommended temperature range

Typical applications:

- Bearings >100 mm (3.9 in.) shaft size
- Outer bearing ring rotation
- Vertical shaft applications
- Continuous high ambient temperatures >35°C
- Propeller shafts
- Agricultural equipment
- Car, truck and trailer wheel bearings
- Large electric motors



Characteristics

Series: LGMT 3

Application: Lubrication - grease **Temperature range:** -30 / 120 °C

Colour: Amber (yellow)
Droping point: > 180 °C
Thickener: Lithium
Base oil type: Mineral oil

Norm: NLGI 3

DIN standard: DIN 51825 K3K-30 **Worked penetration 0.1mm:** 220-250

Volume I	Content kg	Packaging	Article
	1	Can	LGMT3/1
	5	Can	LGMT3/5
	18	Bucket	LGMT3/18
0.42		Cartridge	LGMT3/0.4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

ERIKS