

SKF High load extreme pressure wide temperature range bearing grease LGWA 2

- LGWA 2 is a premium quality mineral oil based, lithium complex grease with extreme pressure (EP) performance. LGWA 2 is recommended for general industrial and automotive applications, when loads or temperatures exceed the range of general purpose greases. Excellent lubrication at peak temperatures up to 220°C for short periods
- Protection of wheel bearings operating under severe conditions
- Effective lubrication in wet conditions
- Good water and corrosion resistance
- Excellent lubrication under high loads and low speeds



Typical applications:

- Wheel bearings in cars, trailers and trucks
- Washing machines
- Fan and electric motors

Characteristics

Series: LGWA 2

Application: Lubrication - grease **Temperature range:** -30 / 140 °C

Colour: Amber (yellow)
Droping point: > 250 °C
Thickener: Lithium-complex
Base oil type: Mineral oil

Norm: NLGI 2

DIN standard: DIN 51825 KP2N-30 **Worked penetration 0.1mm:** 265-295

Volume	Content	Packaging	Article
1	kg		
	1	Can	LGWA2/1
	50	Barrel	LGWA2/50
0.42		Cartridge	LGWA2/0.4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.



1/1 ads 1/1 PR_RC0243_0052_JS_EN_20.04.2024