



SKF Extreme pressure (EP) grease LGEP 2

- LGEP 2 is mineral oil based, lithium soap thickened grease with extreme pressure additives. This grease provides good lubrication in general applications subjected to harsh conditions and vibrations. Excellent mechanical stability
- Extremely good corrosion inhibiting properties
- Excellent EP performance

Typical applications:

- Pulp and paper making machines
- Jaw crushers
- Traction motors for rail vehicles
- Dam gates
- Work roll bearings in steel industry
- Heavy machinery, vibrating screens
- Crane wheels, sheaves
- Slewing bearings



Characteristics

Series: LGEP 2

Application: Lubrication - grease

Temperature range: -20 / 110 °C

Colour: Light Brown

Dropping point: > 180 °C

Thickener: Lithium

Base oil type: Mineral oil

Norm: NLGI 2

DIN standard: DIN 51825 KP2G-20

Worked penetration 0.1mm: 265-295

Volume l	Content kg	Packaging	Article
	1	Can	LGEP2/1
	5	Can	LGEP2/5
	18	Bucket	LGEP2/18
	50	Barrel	LGEP2/50
0.42		Cartridge	LGEP2/0.4

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.