

SKF Hydraulic nut metric thread Series: HMV..E

- Mounting bearings on tapered seatings can be a difficult and time-consuming job. Using an SKF Hydraulic Nut facilitates easy and quick application of the high drive-up forces required for mounting bearings on tapered seatings. Dismounting bearings mounted on either adapter or withdrawal sleeves can also be simplified by using an SKF Hydraulic Nut.Quick connection coupling can be fitted on the face or side of the nut, allowing the nut to be used in areas where space is limited.
- A spare set of piston seals and maintenance kit is supplied as standard.
- Nut supplied with a quick connection coupling to fit the SKF hydraulic pumps.
- Nut equipped with two tommy bars and four mating holes on their front face to facilitate easy nut threading.
- Nut equipped with eyebolts, allowing easy handling.
- Nut equipped with two tommy bars and four mating holes on their front face to facilitate easy nut threading.
- Nut has the starting position of the thread indicated, facilitating easy matching of thread positions on both the nut and mating thread.

Characteristics

Series: HMV..E

Manufacturer ID	Thread size	Article
	mm	
HMV 24E	M 120x2	HMV24E
HMV 30E	M 150x2	HMV30E
HMV 48E	Tr240x4	HMV48E
HMV 64E	Tr320x5	HMV64E

PR_RC0248_0002_EN_25.04.2024

Disclaimer: The content of this document has been composed with the utmost care. However, it is possible that certain information changes over time, becomes inaccurate or incomplete. ERIKS does not guarantee that the information provided on this document is up to date, accurate and complete; the information provided is not intended to be advice. ERIKS shall never be liable for damage resulting from the use of the information provided.

Page 1/1

